



Scientific Inquiry and Review (SIR)

Volume 2, Issue 2, April 2018

ISSN (P): 2521-2427, ISSN (E): 2521-2435

Journal DOI: <https://doi.org/10.29145/sir>

Issue DOI: <https://doi.org/10.29145/sir/22>

Homepage: <https://ssc.umt.edu.pk/sir/Home.aspx>

Journal QR Code:



Article:

Third Order Parallel splitting Method for nonhomogeneous Heat Equation with Integral Boundary Conditions

Author(s):

Syed Ali Mardan
Zakia Hammouch
Muhammad Aziz ur Rehman
Kanwal Tariq

Online Published:

April 2018

Article DOI:

doi.org/10.29145/sir/22/020206

Article QR Code:



Syed Ali Mardan

To cite this article:

Mardan SA, Hammouch Z, Rehman MA, Tariq K. Third order parallel splitting method for nonhomogeneous heat equation with integral boundary conditions. *Sci Inquiry Rev.* 2018;2(2):69–81. DOI: <https://doi.org/10.29145/sir/22/020206>



A publication of the
School of Science
University of Management and Technology
Lahore

Third Order Parallel Splitting Method for Nonhomogeneous Heat Equation with Integral Boundary Conditions

Syed Ali Mardan¹ *, Zakia Hammouch², Muhammad Aziz ur Rehman³ and Kanwal Tariq⁴

^{1,3,4} Department of Mathematics, University of Management and Technology, C-II, Johar Town, Lahore-54590, Pakistan

² Department of Mathematics Faculty of Sciences and Techniques, Moulay Ismail Meknes Morocco

*syedalimardanazmi@yahoo.com

Abstract

A third order parallel algorithm is proposed in this article to solve one dimensional non-homogenous heat equation with integral boundary conditions. For this purpose, we approximate the space derivative by third order finite difference approximation. This parallel splitting technique is combined with Simpson's 1/3 rule to tackle the nonlocal part of this problem. The algorithm developed here is tested on two model problems. We conclude that our method provides better accuracy due to the availability of real arithmetic.

Keywords: parabolic partial differential equation, non-local boundary conditions, finite difference scheme, integral boundary condition.

1. Introduction

Partial differential equations (PDEs) with initial/boundary conditions (IBC) emerge from the mathematical models of real world problems. The PDEs often appear as mathematical equations relating various quantities and their derivatives, e.g., the movement of a particle in a straight line, the movement of a rocket, heat transition, vibration of a molecule and change in the molecular composition of a substance etc. Each one of these problems is represented by an elliptic, hyperbolic or parabolic partial differential equation (PPDE) and could be homogenous, in one, two or three dimensions with non-local boundary conditions (NLBC) along with initial conditions existing in the prose. In the family of PDEs, one of the most important class is PPDEs with NLBC. This class has been studied by different authors. In real life problems, parabolic equations with integral boundary conditions have a number of applications and sometimes we require only their numerical solutions. Thus PPDEs with NLBC have a considerable impact in fields like electrochemistry, biological and medical sciences and population dynamics [1]. The study of PPDEs with IBC is a well-motivated problem. Whenever it is difficult to develop a mathematical model which contains PPDEs, then nonlocal conditions are widely used in the development of such models pertaining to different physical phenomena [2]. The integral IBCs are the generalized form of discrete but regular IBCs. More specifically, when the boundaries are inaccessible then nonlocal conditions arise

during modeling. These partial differential equations are solved by using explicit and Nikolson finite difference (FD) scheme by various authors. Richardson [3] developed the FD technique to solve PDEs. Hartree and Womersley [4] proposed the solution of a PDE with some boundary conditions (BC) using FD approximation. The FD techniques are made by using Taylor expansion. Cannon [5] and Batten [6] independently discuss the development of nonlocal BC PPDEs. Kamynin [7] and Ionkin [8] investigated PPDEs with nonlocal BC for their numerical treatment. Such conditions appear in the modeling of plasma physics, thermal elasticity, heat transmission theory etc [9, 10]. This is the reason PPDEs with NLBC have gained a particular significance in the past and also in the present era. In order to tackle integral conditions which appeared in PDEs many techniques have been proposed in literature and some of these include finite element method, boundary element procedure, spectral schemes, Adomian decomposition approach and the semi-discretization technique [11, 12, 13, 14]. Dehghan [15] proposed three-level explicit finite difference method for the solution of wave 2 equation that merges integral and Neumann condition. Ang [16] developed a numerical technique for solving wave equation with NLBC whose basic assumption is an integro-differential equation and localized interpolating functions. Ramezani and his coworkers [17] introduced another numerical technique by combining FD and the spectral method to obtain numerical solutions of hyperbolic equations subject to NLBC. Bouziani and Benourar [18] studied a mixed PDE which more likely belongs to the class of hyperbolic equations with NLBC in terms of its numerical solution. Cannon and Lin [19, 20] provided a theoretical approach for the solution of PPDEs with NLBC. Dehghan utilized FD schemes [21, 22] and changed Tau method [23] for the solution of a related problem. Now we present the model problem described here. The one dimensional non homogeneous heat equation is given by

$$\frac{\partial u}{\partial t} - \frac{\partial^2 u}{\partial x^2} + u = \zeta(x, t), \quad x \in (0, 1), \quad 0 < t < T \quad (1)$$

with the initial condition

$$u(0, t) = F(x), \quad x \in (0, 1), \quad 0 < t \leq T, \quad (2)$$

and the NBCs

$$\int_0^1 u(x, t) = \sigma_1(t), \quad 0 < t < T, \quad (3)$$

$$\int_0^1 \varphi(x)u(x, t) = \sigma_2(t), \quad 0 < t < T. \quad (4)$$

where $\zeta(x, t), F(x), \sigma_1(t), \sigma_2(t), \varphi(x)$ are known and T is a given constant. Different examples of related problems of parabolic equations have been taken into account by many authors [24, 25, 26]. Taj et al. [27] proposed the numerical technique for the solution of PPDEs by utilizing FD scheme and Pade approximation. Rehman et al. [28] proposed the solution of PPDEs with NLBC by combining parallel method with Simpson's 1/3 rule. Following a similar approach, we will utilize Simpson's 1/3 rule for NLBC by combining it with parallel splitting algorithm to obtain a system of z linear ordinary differential equations. The Pade's approximation will be used to approximate matrix exponential function [27].

2. Non Local Boundary Conditions Treatment

Let us take a positive odd integer $z \geq 9$ and split spatial range $[0, 1]$ into further $z + 1$ intervals of length h provided that $(z + 1)h = X$. Let us also split the open ended variable of time t into subintervals of length l which results into a rectangular mesh having coordinates $(x_E, z_n) = (mh, nl)(m = 0, 1, 2, \dots, z, z + 1)$ and $(n = 0, 1, 2, 3, \dots)$, provided a region $R = [0 < x < 1] \times [t > 0]$ of mesh points and its boundary ∂R involving lines $x = 0, x = 1$ and $t = 0$. Consider third order FD scheme given by

$$\frac{\partial^2 u(x, t)}{\partial x^2} = \frac{1}{12} h^2 \{11u_{j-1} - 20u_j + 6u_{j+1} + 4u_{j+2} - u_{j+3}\} - \frac{h^4}{90} \frac{\partial^6 u(x, t)}{\partial x^6} + O(h^5),$$

as $h \rightarrow 0, j=1, 2, \dots, z-2$ (5)

By applying Eq. (5) in equation Eq. (1), we get a compact form as follows

$$\frac{d^2 u_j}{dx^2} = \frac{1}{12h^2} \{11u_{j-1} - 20u_j + 6u_{j+1} + 4u_{j+2} - u_{j+3}\} + \zeta_j \quad (6)$$

This system of ordinary differential equations is valid only for the mesh points $(x, t) = (xm, tn)$ with $m = 1, 2, \dots, z-2$. Hence we need to develop special FD approximations for remaining mesh points in order to get the same accuracy. So, for $m = z-1, z$ the third order FD schemes with the same accuracy are given by

$$\frac{\partial^2 u(x, t)}{\partial x^2} = \frac{1}{12} h^2 \{u_{j-3} - 6u_{j-2} + 26u_{j-1} - 40u_j + 21u_{j+1} - 2u_{j+2}\} + O(h^5), \quad \text{as } h \rightarrow 0 \quad (7)$$

and

$$\frac{\partial^2 u(x, t)}{\partial x^2} = \frac{1}{12} h^2 \{2u_{j-4} + 11u_{j-3} + 24u_{j-2} - 14u_{j-1} - 10u_j + 9u_{j+1}\} - \frac{h^4}{90} \frac{\partial^6 u(x, t)}{\partial x^6} + O(h^5), \quad \text{as } h \rightarrow 0 \quad (8)$$

By applying Eqs. (6) and (7) in equation Eq. (1), we obtain two differential equations

$$\frac{d^2 u_{z-1}}{dx^2} = \frac{1}{12h^2} \{u_{j-3} - 6u_{j-2} + 26u_{j-1} - 40u_j + 21u_{j+1} - 2u_{j+2}\} + \zeta_{z-1} \quad (9)$$

and

$$\frac{d^2 u_z}{dx^2} = \frac{1}{12} h^2 \{2u_{j-4} + 11u_{j-3} + 24u_{j-2} - 14u_{j-1} - 10u_j + 9u_{j+1}\} + \zeta_z, \quad (10)$$

At any time level $t = tn$, we get a system of z linear ordinary differential equations with $z+2$ unknowns functions U_0, U_1, \dots, U_{z+1} which emerge by applying FD approximations to our model problem. The NLBC in Eqs. (4) and Eq. (4) are tackled with the help of Simpson's 1/3 rule in the following way [28],

$$u_0 = \frac{h}{3} \left\{ \phi_0 u_0 + 4 \sum_{j=1}^{\frac{z+1}{2}} \phi_{2j-1} u_{2j-1} + 2 \sum_{j=1}^{\frac{z+1}{2}-1} \phi_{2j} u_{2j} + \phi_{z+1} u_{z+1} \right\} + \sigma_1(t), \quad (11)$$

and

$$u_1 = \frac{h}{3} \left\{ \psi_0 u_0 + 4 \sum_{j=1}^{\frac{z+1}{2}} \psi_{2j-1} u_{2j-1} + 2 \sum_{j=1}^{\frac{z+1}{2}-1} \psi_{2j} u_{2j} + \psi_{z+1} u_{z+1} \right\} + \sigma_1(t), \quad (12)$$

In the next few lines we will elaborate the development of system of ordinary linear differential equations for $z = 11$. Putting $z=1,2,3,\dots,9$ in Eq. (6) respectively, we get

$$\frac{du_1}{dt} = \frac{1}{12h^2} \{11u_0 - (20 + 12h^2)u_1 + 6u_2 + 4u_3 - u_4\} + \zeta_1 \quad (13)$$

$$\frac{du_2}{dt} = \frac{1}{12h^2} \{11u_1 - (20 + 12h^2)u_2 + 6u_3 + 4u_4 - u_5\} + \zeta_2 \quad (14)$$

$$\frac{du_3}{dt} = \frac{1}{12h^2} \{11u_2 - (20 + 12h^2)u_3 + 6u_4 + 4u_5 - u_6\} + \zeta_3 \quad (15)$$

$$\frac{du_4}{dt} = \frac{1}{12h^2} \{11u_3 - (20 + 12h^2)u_4 + 6u_5 + 4u_6 - u_7\} + \zeta_4 \quad (16)$$

$$\frac{du_5}{dt} = \frac{1}{12h^2} \{11u(4,t) - (20 + 12h^2)u_5 + 6u_6 + 4u_7 - u_8\} + \zeta_5 \quad (17)$$

$$\frac{du_6}{dt} = \frac{1}{12h^2} \{11u(5,t) - (20 + 12h^2)u_6 + 6u_7 + 4u_8 - u_9\} + \zeta_6 \quad (18)$$

$$\frac{du_7}{dt} = \frac{1}{12h^2} \{11u(6,t) - (20 + 12h^2)u_7 + 6u_8 + 4u_9 - u_{10}\} + \zeta_7 \quad (19)$$

$$\frac{du_8}{dt} = \frac{1}{12h^2} \{11u(7,t) - (20 + 12h^2)u_8 + 6u_9 + 4u_{10} - u_{11}\} + \zeta_8 \quad (20)$$

$$\frac{du_9}{dt} = \frac{1}{12h^2} \{11u_8 - (20 + 12h^2)u_9 + 6u_{10} + 4u_{11} - u_{12}\} + \zeta_9 \quad (21)$$

and putting $z = 10$ in Eq. (6)

$$\frac{du_{10}}{dt} = \frac{1}{12h^2} \{u_7 - 6u_8 + 26u_9 - (40 + 12h^2)u_{10} + 21u_{11} - 2u_{12}\} + \zeta_{10} \quad (22)$$

similarly putting $z = 11$ in Eq. (7)

$$\frac{du_{11}}{dt} = \frac{1}{12h^2} \{2u_7 - 11u_8 + 24u_9 - 14u_{10} - (40 + 12h^2)u(11,t) + 9u_{12}\} + \zeta_{11} \quad (23)$$

In this way, we can generalize the algorithm and the system of equation can be written in matrix-vector form as

$$\frac{dU(t)}{dt} = AU(t) + v(t), \quad t > 0 \quad (24)$$

and the initial condition will transform as

$$U(0) = G \quad (25)$$

Here $U(t) = [u_1(t), u_2(t), \dots, u_N(t)]^T$, $X = [g(x_1), g(x_2), \dots, g(x_N)]^T$, where T denotes transpose and coefficient matrix will transform as

$$A = \frac{1}{12h^2} \begin{bmatrix} \eta_2' & \eta_2' & \eta_3' & \eta_4' & \eta_5' & \eta_6' & \eta_7' & L & \eta_{z-1}' & \eta_z' \\ 11 & \varepsilon & 6 & 4 & -1 & & & L & & \\ & 11 & \varepsilon & 6 & & 4 & & -1 & & \\ O & O & O & O & O & O & O & O & O & \\ & -1 & 16 & -30 & & 16 & & -1 & & \\ \gamma_1' & \gamma_2' & \gamma_3' & \gamma_4' & & \gamma_5' & & L & & \gamma_N' \\ \delta_1' & \delta_2' & \delta_3' & \delta_4' & & \delta_5' & & L & & \delta_N' \end{bmatrix}_{N \times N} \quad (26)$$

The quantities in the matrix are given by

$$\xi = -20 - 12h^2$$

Where

$$\eta_1' = 11E_1 - 20 - 12h, \eta_2' = 11E_2 + 6, \eta_3' = 11E_3 + 4, \eta_4' = 11E_4 - 1, \eta_i' = 11E_i, \text{ for } i \geq 7,$$

$$\mu_{z-3} = -D_{z-3} + 11, \mu_{z-2} = -D_{z-2} - 20, \mu_{z-1} = -D_{z-1} + 6, \mu_z = -D_z + 4,$$

and $\mu_i = -D_i$, for $1 \leq i \leq z-4$

$$v_{z-4} = -2D_{z-4} + 1, v_{z-3} = -2D_{z-3} - 6, v_{z-2} = -2D_{z-2} + 26, v_{z-1} = -2D_{z-1} + 1, v_z = -2D_z + 21$$

and $v_i = -2D_i$, for $1 \leq i \leq z-5$

$$w_{z-4} = 9D_{z-4} + 2, w_{z-3} = 9D_{z-3} - 11, w_{z-2} = 9D_{z-2} - 10, w_{z-1} = 9D_{z-1} - 14, w_z = 9D_z - 10 - 12h^2$$

and $w_i = 9D_i$, for $1 \leq i \leq z-4$

$$E_i = \begin{cases} \frac{\frac{4h}{3}(C_4 - C_2 b_i)}{C_1 C_4 - C_2 C_3} & \text{for } i=1,3,\dots,z \\ \frac{\frac{2h}{3}(C_4 - C_2 b_i)}{C_1 C_4 - C_2 C_3} & \text{for } i=2,4,\dots,z-1 \end{cases}$$

and

$$D_i = \begin{cases} \frac{\frac{4h}{3}(C_3 - C_1 b_i)}{C_1 C_4 - C_2 C_3} & \text{for } i=1,3,\dots,z \\ \frac{\frac{2h}{3}(C_3 - C_1 b_i)}{C_1 C_4 - C_2 C_3} & \text{for } i=2,4,\dots,z-1 \end{cases}$$

Here

$$c_1 = -\frac{h}{3}, c_2 = -\frac{h}{3}, c_3 = -\frac{h}{3}\varphi_0 \text{ and } c_4 = -\frac{h}{3}\varphi_z, \text{ also } b_i = b(ih)$$

The column matrix contains factors from the functions $\zeta(x,t)$, $\sigma_1(t)$ and $\sigma_2(t)$ and is given as the

$$v(t) = \left[\frac{9l_1}{12h^2} + \zeta_1, 0, \dots, 0, \frac{-l_2}{12h^2} + \zeta_{z-2}, \frac{-2l_2}{12h^2} + \zeta_z \right]^T$$

where

$$l_1 = \frac{C_2\sigma_2(t) - C_4\sigma_1(t)}{C_1C_4 - C_2C_3}$$

and

$$l_2 = \frac{C_3\sigma_2(t) - C_1\sigma_1(t)}{C_1C_4 - C_2C_3}$$

The solution of system (15) with (2) is given by [27]

$$U(t) = \exp(lA)U(0) + \int_0^{t+l} \exp[(t+l-s)A]v(s)ds \quad (27)$$

which satisfies the repeat connection

$$U(t+l) = \exp(lA)U(t) + \int_0^{t+l} \exp[(t+l-s)A]v(s)ds \quad t=0, 1, 2l, \dots \quad (28)$$

To surmise the lattice exponential in (2), we utilize the normal approximation for genuine scalar (θ) which is of the shape

$$E_3\theta = \frac{b_0 + b_1\theta + b_2\theta^2}{a_0 - a_1\theta + a_2\theta^2 - a_3\theta^3} \quad (29)$$

$$a_3 = \sum_{k=0}^2 (-1)^k \frac{a_k}{(3-k)!} \quad (30)$$

and

$$b_k = \sum_{i=0}^K (-1)^i \frac{a_i}{(K-i)!}, \quad K = 0, 1, 2, 3, 4 \quad (31)$$

Choosing the estimations of parameters a_1, a_2, a_3 as $\frac{91}{20}, \frac{481}{120}$ and $\frac{1}{100}$ so that the strategy utilizes only real arithmetic when p and q are factorized into straight components. The fundamental term showing up in condition (2) is approximated as

$$\int_t^{t+l} \exp[(t+l-r)A]v(s)ds = w_1v(s_1) + w_2v(s_2) + w_3v(s_3) \quad (32)$$

where $s_1 \neq s_2 \neq s_3$ and W_1, W_2 and W_3 are matrices. We have [27]

$$\int_t^{t+l} \exp[(t+l-s)A]s^{k-1}ds = s^{k-1}{}_jW_j = M_k, \quad k = 1, 2, 3, \quad (33)$$

With

$$M_k = A^{-1} \{t^{k-1} \exp(lA) - (t+l)^{k-1} I + (k-1) M_{k-1}\}, k=1,2,3 \quad (34)$$

Taking $s_1 = t$, $s_2 = t + \frac{t}{2}$, $s_3 = t + l$. Using $\theta = lA$ in (30) and taking $e^{lA} = \frac{P}{Q}$ we have [27]

$$P = (I - a_1 lA + a_2 l^2 A^2 - a_3 l^3 A^3)^{-1} \quad (35)$$

$$Q = I + b_1 lA + b_2 l^2 A^2 \quad (36)$$

$$W_1 = \frac{l}{6} I + (4 - 9a_1 + 12a_2) lAP \quad (37)$$

where $j = 1, 2, 3$

$$p_{6+j} = \frac{1}{\prod_{\substack{i=1 \\ i \neq j}}^3 \left(1 - \frac{r_j}{r_i}\right)} \times \{1 - (1 - 3a_1 + 6a_2) r_j\}$$

where $j = 1, 2, 3$

$$p_{9+j} = \frac{1}{\prod_{\substack{i=1 \\ i \neq j}}^3 \left(1 - \frac{r_j}{r_i}\right)} \times \{1 + (3 - 9a_1 + 12a_2)(1 - 3a_1 + 6a_2) r_j^2\}$$

Hence eq. (2) becomes

$$\begin{aligned} U(t+l) &= A_1^{-1} \left[p_1 U(t) + \frac{1}{6} \left\{ p_4 v(t) + 4p_7 v\left(t + \frac{l}{2}\right) + p_{10} v(t+l) \right\} \right] \\ &+ A_2^{-1} \left[p_2 U(t) + \frac{1}{6} \left\{ p_5 v(t) + 4p_8 v\left(t + \frac{l}{2}\right) + p_{11} v(t+l) \right\} \right] \\ &+ A_3^{-1} \left[p_3 U(t) + \frac{1}{6} \left\{ p_6 v(t) + 4p_9 v\left(t + \frac{l}{2}\right) + p_{12} v(t+l) \right\} \right] \end{aligned}$$

Where $A_i = I - \frac{l}{r_i} A$, $i = 1, 2, 3$.

Hence $U(t+l) = \sum_{i=1}^3 y_i t$

Where y_i , ($i = 1, 2, 3$) are the solutions of the systems?

3. Applications

Here, we will apply the method develop in the above section to two model problems already found in literature.

Example 1

Assume the heat equation

$$\frac{\partial u}{\partial t} - \frac{\partial^2 u}{\partial x^2} + u = 2t + t^2 + x, \quad x \in (0,1), \quad 0 < t < T, \quad (38)$$

with initial condition

$$u(0,t) = x, \quad x \in (0,1), \quad 0 < t \leq T, \quad (39)$$

and the integral BCs

$$\int_0^1 u(x,t) dx = \frac{1}{2} + t^2, \quad 0 < t < T \quad (40)$$

$$\int_0^1 xu(x,t) dx = \frac{1}{3} + \frac{1}{2}t^2, \quad 0 < t < T \quad (41)$$

Table 1. Error table for example 1 with $l=0.00001$

| $l=10^{-5}$ | Exact Solution | Approximate Solution | Relative Error |
|-------------|----------------|----------------------|-------------------------|
| N=7 | 1.124980 | 1.124991 | 9.6736×10^{-6} |
| N=9 | 1.099980 | 1.099906 | 9.6751×10^{-6} |
| N=11 | 1.083313 | 1.083324 | 9.6775×10^{-6} |
| N=13 | 1.071409 | 1.071419 | 9.6287×10^{-6} |
| N=15 | 1.062480 | 1.062492 | 9.5876×10^{-6} |

We can make sure that the exact solution to this problem is $u(x,t) = x + t^2$ [29].

The numerical solution of the problem is obtained by the method described in the above sections for different values of $\ell = 0.00001, 0.0000001$ and $z = 7, 9, 11, 13, 15$. The relative error and absolute error are given in Table 1 and Table 2. The results obtained here are very precise which shows that this method is very accurate.

Example 2

Assume the heat equation

$$\frac{\partial u}{\partial t} - \frac{\partial^2 u}{\partial x^2} + u = (10 - 2x)e^t, \quad x \in (0,1), \quad 0 < t < T, \quad (42)$$

with initial condition

$$u(0,t) = 5 - x, \quad x \in (0,1), \quad 0 < t \leq T, \quad (43)$$

and the integral BCs

$$\int_0^1 u(x,t) dx = \frac{9}{2} + e^t, \quad 0 < t < T \quad (44)$$

$$\int_0^1 xu(x,t) dx = \frac{13}{6} e^t, \quad 0 < t < T \quad (45)$$

The exact solution for the issue is $u(u,t) = (5-x)e^t$ [29]. The numerical solution of the problem is obtained by the method described in the above sections for different values of $l = 0.00001, 0.0000001$ and $z = 7, 9, 11, 13, 15$. The relative error and absolute error are given in Table 3 and Table 4. The results obtained here are very precise which shows that this method is very accurate.

Table 2. Error table for example 1 with $l=0.0000001$

| $l=10^{-7}$ | Exact solution | Approximate Solution | Relative Error |
|-------------|----------------|----------------------|-------------------------|
| N=7 | 1.124999 | 1.125007 | 6.5984×10^{-6} |
| N=9 | 1.099999 | 1.100009 | 8.2648×10^{-6} |
| N=11 | 1.083333 | 1.083344 | 9.6225×10^{-6} |
| N=13 | 1.071428 | 1.071439 | 1.0778×10^{-6} |
| N=15 | 1.062499 | 1.062512 | 1.1567×10^{-6} |

Table 3. Error table for example 2 with $l=0.00001$

| $l=10^{-5}$ | Exact Solution | Approximate Solution | Relative Error |
|-------------|----------------|----------------------|-------------------------|
| N=7 | 12.23215 | 12.23222 | 6.2741×10^{-6} |
| N=9 | 12.23215 | 12.23223 | 6.3084×10^{-6} |
| N=11 | 12.23215 | 12.23222 | 6.3283×10^{-6} |
| N=13 | 12.23215 | 12.23222 | 6.3376×10^{-6} |
| N=15 | 12.23215 | 12.23222 | 6.3432×10^{-6} |

Table 4. Error table for example 2 with $l=0.0000001$

| $l=10^{-7}$ | Exact Solution | Approximate Solution | Relative Error |
|-------------|----------------|----------------------|-------------------------|
| N=7 | 11.21291 | 11.21297 | 5.6001×10^{-6} |
| N=9 | 11.14495 | 11.14503 | 6.9319×10^{-6} |
| N=11 | 11.09965 | 11.09974 | 7.9881×10^{-6} |
| N=13 | 11.06729 | 11.06739 | 8.9277×10^{-6} |
| N=15 | 11.043018 | 11.043012 | 9.5369×10^{-6} |

4. Conclusion and Discussion

In this work, we have developed a new method for solving nonhomogeneous PPDEs with NLBC. A third order FD scheme is deployed to heat equation to get numerical approximations at grid points. Simpson’s 1/3 rule is used to tackle integral boundary conditions which help in the construction of a system z ; ordinary differential equation with Z variables. The main role of Simpson’s 1/3 rule is the elimination of two additional variables which arise due to NLBC. The developed method is applied to two test problems found in literature and the numerical results obtained here are highly accurate due to the use of real arithmetic only. This technique can be easily coded in serial or parallel computing environment.

References

- [1] Degan G. Parabolic equations and thermodynamics. *Quart Appl Math.* 1992;3:523–533.
- [2] Avalishvili G, Avalishvili M, Gordeziani D. On a nonlocal problem with integral boundary conditions for a multidimensional elliptic equation. *Appl Math.* 2011;24:566–571.
- [3] Richardson LF. The approximate arithmetical solution by finite differences of physical problems involving differential equations, with an application to the stresses in a Masonry Dam. *Proc R Soc.* 1911;210:307–357.
- [4] Hartree DR, Womersley JR. A method for the numerical or mechanical solution of certain types of partial differential equations. *Proc R Soc.* 1937;161:353–366.
- [5] Canon JR. The solution of the heat equation subject to the specification of energy. *Quart Appl Math.* 1963;21:155–160.
- [6] Batten JG. Second-Order correct boundary conditions for the numerical solution of the mixed boundary problem for parabolic equations. *Math Comp.* 1963;17:405–413.

- [7] Kamynin LI. A boundary value problem in the theory of the heat conduction with non-classical boundary condition. *USSR Comput Math Phys.* 1964;4:33–59.
- [8] Ionkin NI, Moiceev EI. The solutions of certain boundary value problem of the heat conduction theory with non-classical boundary condition. *Differ Uravan.* 1977;13:294–304.
- [9] Samarskii AA. Some problems in differential equations theory. *Differ Equations AMS J.* 1980;16:1925–1935.
- [10] Shi P, Shilor M. On design of contact patterns in one-dimensional thermoelasticity, in theoretical aspects of industrial design. *SIAM Proc.* 1992;76–82.
- [11] Dehghan M. Numerical solution of a parabolic equation with non-local boundary specifications. *Appl Math Comput.* 2003;145:185–194.
- [12] Dehghan M. The use of Adomian decomposition method for solving the one-dimensional parabolic equation with non-local boundary specifications. *Appl Math Comput.* 2004;81:25–34.
- [13] Dehghan M. Efficient techniques for the second-order parabolic equation subject to nonlocal specifications. *Appl Numer Math.* 2005;52:39–62.
- [14] Dehghan M. Solution of a partial integro-differential equation arising from viscoelasticity. *Int J Comput Math.* 2006;83:123–129.
- [15] Dehghan M. On solution of an initial-boundary value problem that combines Neumann and integral condition for the wave equation. *Numer Methods Partial Differ Equations.* 2005;21:24–40.
- [16] Ang WT. A numerical method for the wave equation subject to a nonlocal conservation condition. *Appl Numer Math.* 2006;56:1054–1060.
- [17] Ramezani M, Dehghan M, Razzaghi M. Combined finite difference and spectral methods for the numerical solution of hyperbolic equation with an integral condition. *Numer Methods Partial Differ Equations.* 2007;24:1–8.
- [18] Bouziani A, Benouar NE. Problem mixt avec conditions integrals pour uneclasse d'equations paraboliques. *C R Acad Sci.* 1995;321:1177–1182.
- [19] Cannon JR, Lin Y. Determination of a parameter $p(t)$ in some quasilinear parabolic differential equations. *Inverse Probl.* 1988;4:35–45.
- [20] Cannon JR, Lin Y. Determination of parameter $p(t)$ in Holder classes for some semi-linear parabolic equations. *Inverse Probl.* 1988;4:595–606.
- [21] Dehghan M. Numerical solution of one-dimensional parabolic inverse problem. *Appl Math Comput.* 2003;136:333–334.

- [22] Dehghan M. Parameter determination in a partial differential equation from the over specified data. *Math Comput Model.* 2005;41:196–213.
- [23] Dehghan M. A Tau method for the one-dimensional parabolic inverse problem subject to temperature over specification. *Comput Math Appl.* 2006;52:933–940.
- [24] Cannon JR, Lin Y. A Galerkin procedure for diffusion equations with boundary integral conditions. *Int J Eng Sci.* 1990;28:579–587.
- [25] Cannon JR, Prez-Esteva S, van der Hoek JA. A Galerkin procedure for the diffusion equation subject to the specification of mass. *SIAM J Numer Anal.* 1987;24:499–515.
- [26] Gumel AB. On numerical solution of the diffusion equation subject to the specification of mass. *J Aust Math Soc Ser B.* 1999;40:475– 483.
- [27] Taj MSA, Twizell EH. A family of third-order parallel splitting methods for parabolic partial differential equations. *Int J Comput Math.* 1996;67:411–433.
- [28] Rehman MA, Taj MSA. Fourth-order method for nonhomogeneous heat equation with nonlocal boundary conditions. *Appl Math Sci.* 2009;3:1811–1821.
- [29] Jaradata HM, Jaradate MMM, Alsayyedd O. et al. A new numerical method for heat equation subject to integral specifications. *Nonl Sci Appl.* 2016;9:2117–2125.